containg to 1907/2000/EC, Article

*Printing date 24.06.2022* 

Version: 3 (replaces version 2)

Revision: 24.06.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: Methanol Standard 2

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Application of the substance / the mixture calibration standard

· 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Alivion AG Holzhäusernstrasse 18 CHG-6313 Menzingen Tel. + 41 41 511 46 71 www.alivion.ch E-Mail: info@alivion.ch

• Further information obtainable from: E-Mail: info@alivion.ch

· 1.4 Emergency telephone number:

Tox Info Suisse:145/24 h

Emergency phone number: + 41 44 151 51 51 (24h/7d)

#### **SECTION 2: Hazards identification**

• 2.1 Classification of the substance or mixture • Classification according to Regulation (EC) No 1272/2008

GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- Hazard pictograms



· Signal word Danger

· Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

· Precautionary statements

Trecautionary state	ements
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No
	smoking.
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.
P280	Wear protective gloves / eye protection / face protection.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with
	water [or shower].
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

(Contd. on page 2)

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

	(Contd. of page 1)
· Labelling of packages where the contents do not exceed 125 ml	
· Hazard pictograms	
GHS02 GHS07	
· Signal word Danger	
· Hazard statements Void	
· 2.3 Other hazards	
· Results of PBT and vPvB assessment	
• <b><i>PBT</i></b> : Not applicable.	
· <b>vPvB:</b> Not applicable.	
Determination of endocrine-disrupting properties	
78-93-3 butanone	List II

#### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

• Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5	ethanol Flam. Liq. 2, H225 Eye Irrit. 2, H319	50-100%
CAS: 78-93-3 EINECS: 201-159-0 Index number: 606-002-00-3	butanone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	0.1-1%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X	methanol         Image: Structure Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331         Image: Structure Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331         Image: Structure Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331         Image: Structure Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331         Image: Structure Tox Structure Tox. 3, H301; Acute Tox. 3, H331         Image: Structure Tox Structur	<i>≤</i> 0.1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

#### **SECTION 4: First aid measures**

• 4.1 Description of first aid measures

• General information:

Personal protection for the First Aider.

Show this safety data sheet to the attending doctor.

· After inhalation:

If breathed in, move to fresh air. If not breathing, give artifical respiration. Consult a physician. At high dose, fresh air.

- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing:

Rinse out mouth with water.

Do not induce vomiting.

If symptoms persist consult doctor.

· Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

#### • **4.3 Indication of any immediate medical attention and special treatment needed** *No further relevant information available.*

**SECTION 5: Firefighting measures** 

 5.1 Extinguishing media
 Suitable extinguishing agents: Foam
 Carbon dioxide
 Fire-extinguishing powder
 Sand
 For safety reasons unsuitable extin

• For safety reasons unsuitable extinguishing agents: Water with full jet • 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Carbon Monoxide and Carbondioxide Nitrogen oxides (NOx) Sulphur dioxide (SO2) sodium oxides. • **5.3 Advice for firefighters** 

- · Protective equipment: In case of fire, wear self-contained respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system. Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

#### **SECTION 6:** Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures Beware of vapors accumulating to form explosive concentrations. Ensure adequate ventilation Keep away from ignition sources. Do not breathe vapors / mist / gas Wear protective clothing. In case of fire. · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water. • 6.3 Methods and material for containment and cleaning up: Send for recovery or disposal in suitable receptacles. Pick up mechanically. Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Covering the drains. · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

#### **SECTION 7: Handling and storage**

#### · 7.1 Precautions for safe handling

Do not inhale mist or vapors. Avoid contact with eyes and skin. Keep receptacles tightly sealed. Carry out work in open spaces. Avoid generation of vapours/aerosols. Wash contaminated clothing.

(Contd. on page 4)

(Contd. of page 2)

<sup>-</sup> CHE

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

(Contd. of page 3)

Preventive skin protection. Wash hands after work and breaks. Do not eat, drink or smoke at work · Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep away from open flames and hot surfaces.

· 7.2 Conditions for safe storage, including any incompatibilities

· Storage:

• **Requirements to be met by storerooms and receptacles:** No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Store in dry conditions. Protect from heat and direct sunlight.

Keep container tightly sealed.

Keep under lock and key or only for experts or their agents.

· Recommended storage temperature: See product label.

· Storage class: 3 CH/(TRGS510) Flammable liquids

· 7.3 Specific end use(s) No further relevant information available.

#### **SECTION 8: Exposure controls/personal protection**

#### · 8.1 Control parameters

· Ingredients with lin	nit values that require monitoring at the workplace:
64-17-5 ethanol	
MAK (Switzerland)	Short-term value: 1920 mg/m <sup>3</sup> , 1000 ppm
	Long-term value: 960 mg/m <sup>3</sup> , 500 ppm
	SSc;
78-93-3 butanone	
MAK (Switzerland)	Short-term value: 590 mg/m <sup>3</sup> , 200 ppm
( ,	Long-term value: 590 mg/m <sup>3</sup> , 200 ppm
	H B SSc;
IOELV (EU)	Short-term value: 900 mg/m <sup>3</sup> , 300 ppm
	Long-term value: 600 mg/m <sup>3</sup> , 200 ppm
67-56-1 methanol	(0.08%)
MAK (Switzerland)	Short-term value: 520 mg/m <sup>3</sup> , 400 ppm
, , ,	Long-term value: 260 mg/m <sup>3</sup> , 200 ppm
	H B SSc;
IOELV (EU)	Long-term value: 260 mg/m³, 200 ppm
	Skin
· Ingredients with bi	ological limit values:
78-93-3 butanone	
BAT (Switzerland)	2 mg/l
	Untersuchungsmaterial/Specimen: Urin/Urine
	Probennahmezeitpunkt/Timeof sampling: Expositionsende bzw. Schichtende
	Biol. Parameter/Biological parameter: 2-Butanon (MEK)
· Additional informa	ttion: The lists valid during the making were used as basis.

lattional inform

· 8.2 Exposure controls

· Appropriate engineering controls Use appropriate local exhaust ventilation.

· Individual protection measures, such as personal protective equipment

• General protective and hygienic measures: Do not eat, drink, smoke or sniff while working. Do not eat or drink while working.

(Contd. on page 5)

CHE

Printing date 24.06.2022

\*

Version: 3 (replaces version 2)

Revision: 24.06.2022

## Trade name: Methanol Standard 2

Immediately remove all soiled and contami	
<i>Immediately remove all solled and contami</i>	(Contd. of page 4)
Wash hands before breaks and at the end of	IJ WORK.
Respiratory protection:	1
Respiratory protection according to EN 14	
when risk assessment indicates the need jo	or air-purifying respiratory protection. a respirator with a full face
mask (according to EN136) with filter type	ABEK must be worn.
Hand protection	
Chemical resistant gloves (EN 374)	
(III)	
Protective gloves	
Trolective gloves	
The glove material has to be impermeable	and resistant to the product/ the substance/ the preparation.
	o the glove material can be given for the product/ the preparation/
the chemical mixture.	
Selection of the glove material on con-	sideration of the penetration times, rates of diffusion and the
degradation	J 1 ,
Material of gloves	
Butyl rubber, BR	
Fluorocarbon rubber (Viton)	
Recommended thickness of the material: $\geq$	BR 0.7 FRM 0.7 mm
	ot only depend on the material, but also on further marks of quality
	cturer. As the product is a preparation of several substances, the
	calculated in advance and has therefore to be checked prior to the
application.	
Penetration time of glove material	
	ed below the penetration time has to be at least 480 minutes
(Permeation according to EN 16523-1:201	
	und out by the manufacturer of the protective gloves and has to be
	and out by the manufacturer of the protective gloves and has to be
THIND FUDI	
observed. Eye/face protection	
Eye/face protection	
Eye/face protection Tightly sealed goggles	
Eye/face protection Tightly sealed goggles according to EN 166.	
Eye/face protection Tightly sealed goggles according to EN 166. Body protection:	
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing	
Eye/face protection         Image: Constraint of the second seco	ing.
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing	ing.
<b>Eye/face protection</b> Tightly sealed goggles according to EN 166. <b>Body protection:</b> Solvent resistant protective clothing Flame retardant antistatic protective clothing	
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemica	al properties
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemica 9.1 Information on basic physical and chemical	al properties
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and chemical General Information	al properties
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and chemical General Information Physical state	al properties emical properties
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemica 9.1 Information on basic physical and che General Information Physical state Colour:	al properties emical properties Fluid
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemica 9.1 Information on basic physical and che General Information Physical state Colour: Odour:	al properties emical properties Fluid Blue Alcohol-like
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour threshold:	al properties emical properties Fluid Blue
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing point:	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined.
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and b	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined.
Eye/face protection Fye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and b range	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined. boiling >78 °C (DIN 51751)
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and b range Flammability	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined.
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and b range Flammability Lower and upper explosion limit	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined. boiling >78 °C (DIN 51751) Flammable.
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour threshold: Melting point/freezing point: Boiling point or initial boiling point and b range Flammability Lower and upper explosion limit Lower:	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined. boiling > 78 °C (DIN 51751) Flammable. 3.5 Vol % (64-17-5 ethanol)
Eye/face protection Tightly sealed goggles according to EN 166. Body protection: Solvent resistant protective clothing Flame retardant antistatic protective clothing SECTION 9: Physical and chemical 9.1 Information on basic physical and che General Information Physical state Colour: Odour: Odour: Melting point/freezing point: Boiling point or initial boiling point and b range Flammability	al properties emical properties Fluid Blue Alcohol-like Not determined. Undetermined. boiling >78 °C (DIN 51751) Flammable.

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

### Trade name: Methanol Standard 2

	(Contd. of page
Flash point:	22 °C (DIN 51755)
Ignition temperature:	425 °C (DIN 51794, 64-17-5 ethanol)
Decomposition temperature:	Not determined.
pH	Not determined.
Viscosity:	
Kinematic viscosity	Not determined.
Dynamic:	Not determined.
Solubility	
water:	Soluble.
Partition coefficient n-octanol/water (log value)	Not determined.
Vapour pressure at 20 °C:	59 hPa (64-17-5 ethanol)
Density and/or relative density	
Density at 20 °C:	$0.848 \text{ g/cm}^3$
Relative density	Not determined.
Vapour density	Not determined.
9.2 Other information	
Appearance:	
Form:	Fluid
Important information on protection of health an	d
environment, and on safety.	
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.
Solvent content:	
Organic solvents:	65.3 %
Water:	20.5 %
VOC (EC)	65.32 %
VOC (CH)	65.32 %
Change in condition	00.02 /0
Evaporation rate	Not determined.
•	
Information with regard to physical hazard classe	
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Highly flammable liquid and vapour.
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flammable	
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
	17 • 1
Corrosive to metals	Void

#### SECTION 10: Stability and reactivity

· 10.1 Reactivity Vapour/air mixtures are explosive and flammable if heated to a high degree.

· 10.2 Chemical stability

\*

The product is chemically stable under normal ambient conditions (room temperature).

(Contd. on page 7)

CHE

ccording to 1907/2006/EC, Article

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

(Contd. of page 6)

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: Strong oxidizing agents, Gum. different plastics. magnesium, zinc alloys.

• 10.6 Hazardous decomposition products: Carbon monoxide and carbon dioxide Nitrogen oxides (NOx)

Sulphur dioxide

In the event of a fire, hazardous decomposition products may be formed.

#### **SECTION 11: Toxicological information**

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Heat, flames and sparks. • Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:		
64-17-5 et	hanol	
Oral	LD50	10,470 mg/kg (rat)
Dermal	LD50	>2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	51 mg/l (rat)
67-56-1 methanol		
Oral	LD50	100.1 mg/kg (rat)
Dermal	LD50	300.1 mg/kg (rabbit)
Inhalative	LC50/4 h	3.1 mg/l (rat)
78-93-3 bi	itanone	
Oral	LD50	>2,193 mg/kg (rat)
Dermal	LD50	>5,000 mg/kg (rabbit)
Inhalative	LC50/4 h	34 mg/l (rat)
		tion Based on available data, the classification criteria are not met.
		irritation Causes serious eye irritation.
· Respirator	y or skin s	ensitisation Based on available data, the classification criteria are not met.
		ity Based on available data, the classification criteria are not met.
· Carcinoge	nicity Base	ed on available data, the classification criteria are not met.
· Reproduct	ive toxicity	Pased on available data, the classification criteria are not met.
· STOT-sing	gle exposu	re Based on available data, the classification criteria are not met.
		sure Based on available data, the classification criteria are not met.
-		used on available data, the classification criteria are not met.
• 11.2 Infor	mation on	other hazards
<b>F</b> 1 ·	1	.•

· Endocrine disrupting properties

78-93-3 butanone

List II

 SECTION 12: Ecological information

 · 12.1 Toxicity

 • Aquatic toxicity:

 64-17-5 ethanol

 EC50 4 h
 5,800 mg/l (Bakterien)

 LC50 (96h)
 15,300 mg/l (pimelas promelas)

 EC 50 (72 h)
 275 mg/l (Chlorella vulgaris)

 EC50 48 h
 12,340 mg/l (daphnia magna)

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

67-56-1 methanol EC50 96 h OECD 202 LC50 (96h)		ng/l (daphnia magna)	
LC50 (96h)			
( )	15,400 mg/l (Lepomis macrochirus)		
ErC50 96 h		22,000 mg/l (Pseudokirchneriella subcapitata Grünalg)	
78-93-3 butanone	,		
<i>LC50 (96h)</i> 308 mg/l (daphnia magna)		l (daphnia magna)	
		g/l (pimelas promelas)	
EC50 (16h) 1,150 mg/l (Pseuomonas putida)			
EC 50 (72 h)	1	g/l (Pseudokirchneriella subcapitata Grünalg)	
<b>12.2 Persistence and a</b> Easily biodegradable	legradabi	lity	
64-17-5 ethanol			
Biologische Abbaubarlkeit 15 d 98 %		98 %	
BSB		930-1,670 mg/g	
12.4 Mobility in soil N 12.5 Results of PBT a PBT: Not applicable. vPvB: Not applicable. 12.6 Endocrine disrup 12.7 Other adverse efj Additional ecological General notes: Water hazard class 1 (	to further nd vPvB of pting prop fects informati (German 1	<b>verties</b> For information on endocrine disrupting properties see section 11.	

· Recommendation

Hand over to hazardous waste disposers.

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

14 06 03\* other solvents and solvent mixtures

15 01 02 plastic packaging

DETEC Ordinance on Lists for the Movement of Waste (SR 814.610.1)

14 06 03 sw special waste other solvents and solvent mixtures

15 01 02: plastic packaging

• Uncleaned packaging:

- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

### SECTION 14: Transport information

· 14.1 UN number or ID number · ADR, IMDG, IATA

UN1987

· 14.2 UN proper shipping name · ADR

1987 ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL)), special provision 640D

(Contd. on page 9)

CHE

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

### Trade name: Methanol Standard 2

	(Contd. of page
IMDG	ALCOHOLS, N.O.S. (ETHANOL (ETHYL ALCOHOL))
	ALCOHOLS, N.O.S. (ETHANOL)
14.3 Transport hazard class(es)	
ADR, IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR, IMDG, IATA	II
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	33
EMS Number:	F-E,S-D
Stowage Category	В
14.7 Maritime transport in bulk according to IM instruments	
	Not applicable.
Transport/Additional information:	
ADR	11
Limited quantities (LQ) Excepted quantities (EQ)	1L Code: E2
Excepted quantities (EQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	1 71 1 0 0
UN "Model Regulation":	UN 1987 ALCOHOLS, N.O.S., SPECIAL PROVISIO
	640D (ETHANOL (ETHYL ALCOHOL)), 3, II

#### **SECTION 15: Regulatory information**

• 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture • Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

• Hazard pictograms



Signal word Danger
Hazard statements
H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.

(Contd. on page 10)

<sup>-</sup> CHE

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

#### Trade name: Methanol Standard 2

	(	Contd. of page 9)
· Precaution	ary statements	
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition smoking.	n sources. No
P241	Use explosion-proof [electrical/ventilating/lighting] equipment.	
P280	Wear protective gloves / eye protection / face protection.	
P303+P361	I+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. R. water [or shower].	inse skin with
P305+P351	1+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove con present and easy to do. Continue rinsing.	tact lenses, if
P501	Dispose of contents/container in accordance with local/regional/national, regulations.	/international
· Directive 20	012/18/EU	
· Named dan	<b>agerous substances - ANNEX I</b> None of the ingredients is listed. <b>agory</b> P5c FLAMMABLE LIQUIDS	
· Qualifying · Qualifying	<i>quantity (tonnes) for the application of lower-tier requirements</i> 5,000 <i>t</i> <i>quantity (tonnes) for the application of upper-tier requirements</i> 50,000 <i>t</i> <i>TON (EC) No 1907/2006 ANNEX XVII</i> Conditions of restriction: 3	
	/E 2011/65/EU on the restriction of the use of certain hazardous substances in a equipment – Annex II	electrical and
None of the	ngredients is listed.	
· REGULAT	TON (EU) 2019/1148	
· Annex I - I under Artic	<b>RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose</b> cle 5(3))	e of licensing
None of the	e ingredients is listed.	
	REPORTABLE EXPLOSIVES PRECURSORS	
None of the	e ingredients is listed.	
· Regulation	(EC) No 273/2004 on drug precursors	
78-93-3 bu		3
	e (EC) No 111/2005 laying down rules for the monitoring of trade between the Co ries in drug precursors	mmunity and
78-93-3 bu	itanone	3
	Switzerland (CH)	
	cidents Ordinace MAO SR 814.012: threshold quantities 20000 kg Chim SR 813.11 : No group	
	ical safety assessment: A Chemical Safety Assessment has not been carried out.	
<b>SECTIO</b>	N 16: Other information	
	nation is based on our present knowledge. However, this shall not constitute a guar oduct features and shall not establish a legally valid contractual relationship.	antee for any

- · Department issuing SDS: product safety department
- · Contact: MADER CHEMIE SICHERHEIT CH-3006 Bern Hr. Mader • Date of previous version: 23.06.2022 • Version number of previous version: 2 · Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 11)

CHE

CHE

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 24.06.2022

Version: 3 (replaces version 2)

Revision: 24.06.2022

# Trade name: Methanol Standard 2

(Contd. of page 10) VOCV: Lenkungsabgabe auf flüchtigen organischen Verbindungen, Schweiz (Swiss Ordinance on volatile organic compounds) VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity – Category 3
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
• * Data compared to the previous version altered.